

Mabanol Argon Fleet 20W-50

High Performance Universal Engine Oil

Application

Mabanol Argon Fleet 20W-50 is a universal engine oil formulated to meet the stringent demands of manufacturers of petrol and diesel engines as well as respective turbo versions and heavy-duty vehicles. Hence, Mabanol Argon Fleet 20W-50 is a suitable oil for the year-round protection of mixed fleets and, as it can be universally applied, has a positive impact on economical storage.

Mabanol Argon Fleet 20W-50 is a mineral oil based universal engine oil.

The viscosity formulation provides outstanding lubrication properties at high operating temperatures and is perfectly suitable for engines with a high mileage program.

Specifications

- SAE grade 20W-50
- ACEA A3/B4, E2
- API CG-4/SL

Approved under a different title

- MB-Approval 228.1
- MAN 271
- Volvo VDS

Properties

Key data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0.888
Dyn. Viscosity at -15°C (CCS)	DIN 51 377	mPa s	9.150
Kin. Viscosity at 40°C	DIN 51 562	mm ² /s	153
Kin. Viscosity at 100°C	DIN 51 562	mm ² /s	16.9
Viscosity Index (VI)	DIN ISO 2909		118
Flash point COC	DIN ISO 2592	°C	245
Pourpoint	DIN ISO 3016	°C	-30
Total base number	DIN ISO 3771	mg KOH/g	9.3
Sulphate ash	DIN 51 575	g/100 g	1.2

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981