

## Mabanol Radon Gear ATF III

### Automatic Transmission Fluid

#### Application

Mabanol Radon Gear ATF III is an automatic transmission fluid conforming to the current General Motors specification Dexron III H. It is recommended for automatic and manual transmissions, auxiliary transmissions, clutch, steering and hydraulic systems. Mabanol Radon Gear ATF III can also be used in automatic transmissions with Mercedes-Benz requirements MB 236.5, MB 236.6 and MB 236.7.

Due to the differing requirements for the coefficient of friction, various ATF types are specified for servicing the automatic transmissions, torque converters and powershift gear boxes fitted in motor vehicles. The vehicle manufacturer's instructions must therefore be observed without fail.

#### Properties

Mabanol Radon Gear ATF III is dyed red.

#### Approvals

- MB-Approval 236.1
- MAN 339 Type V1
- MAN 339 Type Z1

#### Approved under a different title / recommended for

- General Motors Dexron III H
- Voith H55.6335.3x (G 607)
- Volvo 97341
- ZF TE-ML 04D, 14A, 17C
- Caterpillar TO-2
- Allison C4, TES 389
- Ford Mercon

#### Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0.860
Dyn. Viscosity at -40°C	DIN 51 398	mPa s	18.500
Kin. Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	35.7
Kin. Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	7.4
Viscosity Index (VI)	DIN ISO 2909		180
Flash point COC	DIN ISO 2592	°C	216
Pourpoint	DIN ISO 3016	°C	< -50

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987