

## Mabanol Xenon Alpha FO 5W-30

### Synthetic High Performance Low Friction Engine Oil

#### Application

Mabanol Xenon Alpha FO 5W-30 is a high-performance low-friction engine oil designed for use in both petrol and diesel engined passenger cars of the latest generation requiring the respective Ford specifications.

#### Properties

Mabanol Xenon Alpha FO is a synthetic high performance low friction motor oil of viscosity grade 5W-30.

Excellent cold-starting properties guarantee optimal lubrication in the cold running phase as extreme loads and high temperatures are also safely handled under all operating conditions. It ensures very high wear

protection and lower friction losses (HTHS <3.5 mPa s).

Mabanol Xenon Alpha FO 5W-30 further contributes to the protection of the environment owing to its reduced fuel consumption (fuel economy attributes).

#### Specifications

- SAE Grade 5W-30
- ACEA A5/B5

#### Recommended for

- Ford WSS-M2C913-A/B/C/D

#### Approved under a different title

- Jaguar

#### Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0.854
Dyn. Viscosity at -30°C (CCS)	DIN 51 377	mPa s	4.480
Kin. Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	50.8
Kin. Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	9.39
Viscosity Index (VI)	DIN ISO 2909		171
Flash point COC	DIN ISO 2592	°C	236
Pourpoint	DIN ISO 3016	°C	-42
Total base number	DIN ISO 3771	mgKOH/g	11
Sulphate ash	DIN 51 575	g/100g [% w/w]	1.2

Updated in July 2013

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981